

RPS-API



RPS (Remote Programming Software) is the Bosch client application used to program Intrusion Control Panel operations.

The RPS-API (Application Programming Interface) offers a central interface to program one or many Intrusion Control Panels across a Bosch Security System.

Developers integrate using a RESTful web API to read or modify control panel programming directly to the RPS database.

Control panels receive programming updates automatically through an RPS-API Scheduler service, without the need to use the RPS client application.

Functions

Read/Write functions

The following read/write functionality is available:

- Control panel connection details
- Control panel users
- User attributes such as Authority Level, Card Data and more.

Read Only functions

The following read only functionality is available:

- Panel identification and languages
- Area wide parameters
- Point profiles
- Point assignments

Control Functions

The following control functionality is available:

- Panel Arm/Disarm
- Point Bypass/UnBypass

- ▶ Program Bosch Control Panels using your own application interface
- ▶ Automatically send programming updates to one or many control panels
- ▶ Scale efficient panel and user management
- ▶ Increase automation and security of control panel updates

Parts included

The table below shows the contents of the self-extracting zip file.

Quantity	Component
1	RPS-API Installer and HTTPS setup tool
1	Postman collection containing sample REST Calls
1	Application note
1	Specification document

Technical specifications

API version	v2.3.0.6
RPS versions supported	Version 6.11 or higher to support full API and panel operations, including TCP Panel connections. Version 6.04 to RPS 6.10 to support full API features with panel connections limited to and requiring UDP protocol.
Supported API communications	HTTPS [API v2.2 and greater does not support HTTP] Can create a self-signed certificate or install an existing certificate using the API installer and tools.
Control panels supported	B9512G, B8512G B6512, B5512, B4512, B3512 D9412GV4, D7412GV4

- Firmware v1.00 through v1.00.010
- Firmware v2.00 through v2.00.014

D9412GV3, D7412GV3

- Firmware v8.10 through v8.14

MS Windows OS

Windows 8, .NET 4.6

Ordering information

RPS API

Application Programming Interface (API) for interfacing with the RPS Database.

The RPS-API is available through the Bosch Integration Partner Program.

Visit <http://ipp.boschsecurity.com> to become a partner and download the API.

Order number **RPS-API | F03X00000**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Platz 1
D-70839 Gerlingen
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com